

# PATENT ABSTRACTS OF JAPAN

(11)Publication number : 11-245375

(43)Date of publication of application : 14.09.1999

(51)Int.Cl.

B41F 15/40

B41F 15/08

B41F 15/26

H05K 3/12

H05K 3/34

(21)Application number : 10-053174

(71)Applicant : TANI DENKI KOGYO KK

(22)Date of filing : 05.03.1998


(72)Inventor : TANI OKIE

(54) METHOD FOR CONTROLLING SNAP-OFF IN SCREEN PRINTING AND ITS DEVICE

(57)Abstract:

**PROBLEM TO BE SOLVED:** To improve snap-off in screen printing and carry out the printing of high accuracy.

**SOLUTION:** An encircling body 5 formed of a plate with a guide hole 7 encircling a material 2 to be printed is fixed and supported to be lifted and lowered on the face same as the upper face of the material 2 disposed thereon. The material 2 to be printed can be placed on a placing bed 10 and lifted and lowered by a lifting device 8. A screen plate 3 can be lifted and lowered through a frame 4. At the time of snap-off, the screen plate 3 is released just as it is, or the encircling body 5 is lifted and released together with the screen plate, or the material 2 to be printed is lowered by a lifting device 8 simultaneously with the release of the screen plate 3 and released from the screen plate 3.



## LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]